# PMG Code Action Committee
# Working Document for
# 2023-202

Legend:

"Dropped" indicates that Committee decided to drop the item

"Number not used" indicates Working Document item number is not used.

Purple text: staff notes/advisories.

Yellow highlight: details that need attention/review

Aqua highlight: code text work needed or reviewed

Green highlight: proposal entered into cdpACCESS

Purple highlight: cdpACCESS input needs updated

---

TEMPLATE

Item n

Statement of the Issue (beginning of the Reason Statement):

Work Group needed?

Proposed code language

"Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved."

408.3.4 Interlocks. Electrical equipment and appliances used in processes that generate flammable vapors or gases shall be interlocked with ventilation fans so that the equipment cannot be operated unless the exhaust ventilation fans are in operation.

408.4 Exhaust fan discharge. Exhaust fans shall be positioned so that the discharge will not impinge on the roof, other equipment or appliances or parts of the structure. A vertical discharge fan shall be manufactured with an approved drain outlet at the lowest point of the housing to permit drainage of oils or byproducts to an approved location.

408.5 Exhaust fan mounting. Upblast fans serving plant processing or extraction facilities and installed in a vertical or horizontal position shall be hinged, supplied with a flexible weatherproof electrical cable to permit inspection and cleaning and shall be equipped with a means of restraint to limit the swing of the fan on its hinge. The ductwork shall extend not less than 18 inches (457 mm) above the roof surface.

408.6 Clearances. Exhaust equipment serving a plant processing or extraction facilities shall have a clearance to combustible construction of not less than 18 inches (457 mm).

> Exception: Factory-built exhaust equipment installed in accordance with Section 304.1 and listed for a lesser clearance.

408.7 Terminat ion location. The outlet of exhaust equipment serving plant processing or extraction facilities shall be in accordance with Section 501.3 of this code.

> Exception: The minimum horizontal distance between vertical discharge fans and parapet-type building structures shall be 2 feet (610 mm), provided that such structures are not higher than the top of the fan discharge opening.

408.8 Ducts. Exhaust duct construction shall comply with Chapter 6.

408.9 Hazardous Exhaust Systems. When the exhaust system is determined to be a hazardous exhaust system by this code, the International Building Code or the International Fire Code, that system shall be installed in accordance with Section 510 of this code.

502.21 Processing and Extraction Facilities. Processing and extraction Facilities shall be provided with an exhaust system in accordance with of Section 408 of this code and Chapter 39 of the International Fire Code.

502.21.1 Operation. The exhaust system for processing and extraction Facilities shall have controls that operate the system continuously when the space is occupied.

502.21.2 Post-processing. Post-processing operations, including dispensing of flammable liquids between containers, shall be performed within a hazardous exhaust fume hood rated for exhausting flammable vapors and listed in accordance with UL 1805. Electrical equipment used within the hazardous exhaust fume hood shall be rated for use in flammable atmospheres. Exception: A

"Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved."

hazardous exhaust fume hood shall not be required where an approved exhaust system is installed in accordance with NFPA 91.

Add New Standard:

UL
1805-2002: Standard for Laboratory Hoods and Cabinets (Ed.1)

Reason Statement:

“Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved.”

"Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved."

## Item 10 ISPSC Shallow water depth of 33 inches and sun shelfs AND 4 foot depth max.

From the ISPSC:

807.2 Shallow end water depths. The design water depth as measured at the shallowest point in the shallow area shall be not less than 33 inches (838 mm) and not greater than 4 feet (1219 mm). Shallow areas designed in accordance with Sections 809.6, 809.7 and 809.8 shall be exempt from the minimum depth requirement.

## Item 11 NTSB fuel gas detection monitor. IFGC proposal from last cycle.

An IFGC proposal for fuel gas monitor was not found.

## Item 12 ISPSC Minimum horizontal distance of buried pools in relationship to nearby footings.

This would require a new section somewhere in Section 307 GENERAL DESIGN

## Item 13 IPC Use of standard material RPZ for resistance to carbonated water.

Table 608.1 and Section 608.17.1.1 would be involved.

"Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved."

# Item 14 IPC Cleanup errors in Table E103.3(1)

The reported errors are:

1. Row E states "Static Head Loss 21 x 43 psi"

a. Following unit convention from the above rows, 21 should read as ( 21' ).

b. The conversion from feet to psi is .43 psi.

2. The addition of cold water friction loss does not equal what is presented in row K

a. 2.21 + .38 + .38 + 3.08 = 6.05. The table lists 5.93 as the total, which is correct, but not based off the table. The length of BC + equivalent fittings length is = 20 when it should be 15 (the sum of 8+7).

This is leading to error in summing the total friction losses.

From the IPC:

**TABLE E103.3(1)**
**RECOMMENDED TABULAR ARRANGEMENT FOR USE IN SOLVING PIPE SIZING PROBLEMS**

| COLUMN | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
|---|---|---|---|---|---|---|---|---|---|

“Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved.”

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| B | | Highest pressure required at a fixture (Table 604.3) | 15.00 | | | | | | | | |
| C | | Meter O R V V meter | 11.0<br>0 | | | | | | | | |
| D | | Tap in main loss < W D S [Table E103.3(4)] | 1.61 | | | | | | | | |
| E | | Static head loss 21 × 43 psi | 9.03 | | | | | | | | |
| F | | Special fixture loss backflow preventer | 9.00 | | | | | | | | |
| G | | Special fixture loss—Filter | 0.00 | | | | | | | | |
| H | | Special fixture loss—Other | 0.00 | | | | | | | | |

“Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved.”

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| L | Difference (Line J minus Line K) | | | — | — | — | — | — | — | — | 3.43 | |
| | Pipe section (from diagram) | $ ; % ; | 288 | 108.0 | 54 | 2½ | 12.00 | 0.69 | 3.3 | 2.21 | — | |
| | | % ; & ; | 24 | 38.0 | 8 | 2 | 7.5 | 0.16 | 1.4 | 0.22 | — | |
| | Hot water distribution piping | & ; ' ; | 12 | 28.6 | 13 | 1½ | 4.0 | 0.17 | 336.12 | 518tC | 4.0 | |

“Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved.”

“Copyright © 2023/2024/2025/2026 International Code Council, Inc. All rights reserved.”

4